## WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



**WO 88/ 06425** 

## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 4: (11) International Publication Number: A1 A61B 5/02 (43) International Publication Date: 7 September 1988 (07.09.88)

PCT/BE88/00005 (21) International Application Number:

(22) International Filing Date: 22 February 1988 (22.02.88)

8700173 (31) Priority Application Number:

25 February 1987 (25.02.87) (32) Priority Date:

(33) Priority Country:

(71)(72) Applicant and Inventor: VAN DEN BERGHE, René [BE/BE]; Baneike 24, B-9660 Brakel (BE).

(81) Designated States: AT (European patent), AU, BB, BE (European patent), BG, BJ (OAPI patent), BR, CF (OAPI patent), CG (OAPI patent), CH (European patent), CM (OAPI patent), DE (European patent), DK, FI, FR (European patent), GA (OAPI patent), GB (European patent), HU, IT (European patent), JP, KP, KR, LK, LU (European patent), MC, MG, ML (OAPI patent), MR (OAPI patent), MW, NL (European patent). pean patent),

NO, RO, SD, SE (European patent), SN (OAPI patent), SU, TD (OAPI patent), TG (OAPI patent), US.

Published

With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: APPARATUS AND METHOD FOR PRODUCING CRACKERS OF GRANULAR MATERIAL

## (57) Abstract

Apparatus and method for producing shaped products from granular materials, in particular food products from cereals such as rice, corn, wheat or the like, which are pressurebaked and afterwards expanded in a heatable mold defined in a fixed upper mold and a movable lower mold (punch). Preferably the mold comprises a peripheral mold element which is individually movable. Driving means are provided for actuating the movable punch which are in the form of two aligned, separately controlled hydraulic cylinders of which one cylinder defines a precise expansion and the other cylinder controls the compression in combination with separate end switch means.

